

GA HAZARD LIGHT FLASHING OR STEADY BURN

The newest barricade light option from OTW has the ability to switch between flashing and steady-burn states, making it our most versatile light. The same batch of lights can be used on multiple jobs even when lighting requirements change. Batteries now come preinstalled so contractors can use the lights right out of the box. The GA Hazard Light is also smaller and lighter than our other models, making it more cost-effective to ship.

The best features, we kept. The light is engineered with a slightly angled lens to direct light upward, the battery recharges in sunlight and the base is designed to screw directly into the 10" Low Profile Barricade, or the 24" Low Profile Barricade when coupled with a basic adapter.

FEATURES & BENEFITS

- Switch to change light state from steady-burn to off to blinking
- Charged light automatically turns on when ambient light falls below 60 lux
- Battery: 1.2v, Sub-C Class, NiMH, 2200 mAh
- Temperature Range: -40°F to +140°F / -40°C to +60°C
- Water and Dust Resistant to IP65 Standard

LIGHT OUTPUT

- 4 Red LED with effective intensity of 8 candela
- Nominal Night Range: 2 miles / 3.2 km
- Vertical Divergence: +/- 5°
- Horizontal Output: 360°

MOVEMENT AREAS: FAA AC 150/5370 - 2G

This FAA advisory circular also calls for "Omni-directional red lights either flashing or steady-burning, collapsible barricades, and/or signs to separate all construction/maintenance areas from the movement areas."

REDUCED VISIBILITY: FAA AC 150/5370 - 2G

"During reduced visibility or night hours, supplement the barricades with red lights, either flashing or steady-burning."



LED COLOR

Red (650 nm)

SIZE

Height: 5.3 in / 13.46 cm
Diameter: 3.5 in / 8.89 cm

WEIGHT

11 oz / 0.313 kg

BATTERY LIFE

Battery comes preinstalled. For best battery life we recommend turning light off when not in use.