

# SMALL JERSEY BARRICADE

## MB32X72JSS

The MB32x72 JSS barricade provides robust dependability for nearly every application. Leveraging the strengths of rotational molding, this barricade has exceptional environmental durability and has been successfully deployed to locations such as northern Alaska and parts of Canada, withstanding severe weather conditions. These parts have been used all over the world, in every possible scenario, and consistently exceed expectations.

Ideal for use in low-speed construction zones, temporary or semi-permanent security applications, and for hazard identification, this is the true workhorse of our barricade line. We offer a variety of heights and weights in order to perfectly match your requirements.

### FEATURES & BENEFITS

- Exceptional environmental durability
- Multi-purpose
- Manufactured in approved OSHA orange
- Can be ballasted with water or sand

### OPTIONAL CUSTOMIZATION

- High-intensity retroreflective sheeting on both sides
- Spin welds accommodate additional hazard lights

### COLORS

Safety orange (custom colors available).

### COMPOSITION

Rotationally molded Linear Low Density Polyethylene (LLDPE).



### SIZE

Height: 32 in / 81.3 cm  
Length: 72 in / 182.9 cm  
Width: 24 in / 61 cm

### WEIGHT

#### Standard

Empty: 75 lb / 34 kg  
Full: Apprx 900 lb / 3406.8 kg

#### Heavy Duty

Empty: 100 lb / 45.4 kg  
Full: Apprx 925 lb / 3501.5 kg  
\*Max recommended water ballast is 100 gallons (weight calculation based on 100 standard US gallons of water)

### PALLET LOADING

Dimensions: 92.5" x 68.5" x 100"  
Capacity: 15 units